M.M. Meyers 1-8 E Serial No. 09/5/0038 **EUROPEAN PATENT O** 

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

61272987

**PUBLICATION DATE** 

03-12-86

APPLICATION DATE

29-05-85

APPLICATION NUMBER

60114065

APPLICANT: HITACHI LTD;

INVENTOR: KAJIMURA TAKASHI;

INT.CL.

: H01S 3/18

TITLE

SEMICONDUCTOR LASER ELEMENT

ABSTRACT: PURPOSE: To prevent the disturbance of the characteristics of luminous radiation by further forming a recessed section so that laser beams projected near a reflecting surface 7 in a semiconductor laser to which the reflecting surface for an optical resonator is shaped are not interrupted by etching, etc.

> CONSTITUTION: A P-side electrode 6 is formed to a semiconductor crystal 10 containing double hetero-structure, and a reflecting surface 7 for a resonator is prepared through ion-beam etching. A photo-resist mask is shaped through photolithography, and a recess in 15µm depth is formed. A distance between the reflecting surface and the recess 9 is brought to approximately 3µm after etching. The back is ground, and etched, an N-side electrode 11 is shaped, and lastly approximately the central section of the recess 9 is scribed, thus preparing a semiconductor laser chip. According to the structure, laser beams emitted from a beam outgoing section 12 are introduced to the outside without receiving noxious reflection, etc.

COPYRIGHT: (C)1986,JPO&Japio